



TGSI'S - 50 Key Features & Benefits

Individual Studs

Pads/Tiles

316 SS Plastic Brass Composite Ceramic 316 SS Rubber PU HDBU Cork/Rubber

| | | | | | | | | | | | |
|-----|--|---|---|---|---|---|---|---|---|---|---|
| 1. | Australian Made & Owned | X | X | X | X | X | X | X | X | X | ✓ |
| 2. | Made in Victoria | X | X | X | X | X | X | X | X | X | ✓ |
| 3. | Good Environmental Choice Australia (G.E.C.A.) Certification | X | X | X | X | X | X | X | X | X | ✓ |
| 4. | Proven in harsh Australian Conditions | ✓ | X | ✓ | X | ✓ | ✓ | X | X | X | ✓ |
| 5. | Green Star Compliant | X | X | X | X | X | X | X | X | X | ✓ |
| 6. | Usable in Green Star Buildings | X | X | X | X | X | X | X | X | X | ✓ |
| 7. | R 11 Slip Resistant or Better | ✓ | ✓ | ✓ | ✓ | X | ✓ | ✓ | X | ✓ | ✓ |
| 8. | Highly durable able to withstand | | | | | | | | | | |
| 9. | Heavy pedestrian traffic | ✓ | X | ✓ | ✓ | ✓ | ✓ | X | ✓ | ✓ | ✓ |
| 10. | Ability to absorb force at point of impact. | ✓ | X | ✓ | ✓ | ✓ | ✓ | X | ✓ | ✓ | ✓ |
| 11. | Low V.O.C.'s (Volatile Organic Compounds) | ✓ | X | ✓ | X | ✓ | ✓ | X | X | ✓ | ✓ |
| 12. | Quiet underfoot | X | X | X | X | X | X | ✓ | X | ✓ | ✓ |
| 13. | Cheap to buy | X | ✓ | X | X | ✓ | X | ✓ | ✓ | X | X |
| 14. | Easy to install | X | ✓ | X | X | X | X | X | X | ✓ | ✓ |
| 15. | Color Hold Resist Fade | ✓ | X | ✓ | X | ✓ | ✓ | X | X | ✓ | ✓ |
| 16. | Large Stock Holdings | ✓ | ✓ | X | X | ✓ | X | X | X | ✓ | ✓ |
| 17. | Fast Installation | X | X | X | X | X | ✓ | X | ✓ | ✓ | ✓ |
| 18. | No Edge Trip Hazard | ✓ | ✓ | ✓ | ✓ | X | X | X | X | X | X |
| 19. | High Luminous Contrast | X | X | X | X | X | X | ✓ | ✓ | ✓ | ✓ |
| 20. | Internal Use | ✓ | ✓ | ✓ | ✓ | X | ✓ | ✓ | ✓ | ✓ | ✓ |
| 21. | External Use | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | X | ✓ | ✓ | ✓ |
| 22. | No Installation Downtime | X | ✓ | X | X | X | ✓ | ✓ | ✓ | ✓ | ✓ |
| 23. | Easy Maintain/Replace | X | X | X | X | X | ✓ | X | ✓ | ✓ | ✓ |
| 24. | Will not Fracture | ✓ | X | ✓ | X | X | ✓ | ✓ | X | ✓ | ✓ |
| 25. | Crack Resistant | ✓ | X | ✓ | X | X | ✓ | X | X | ✓ | ✓ |
| 26. | Chip Resistant | ✓ | X | ✓ | X | X | ✓ | ✓ | X | ✓ | ✓ |
| 27. | Low Formaldehyde Emissions | ✓ | X | ✓ | X | ✓ | ✓ | ✓ | X | ✓ | ✓ |
| 28. | Critical Radiant Flux Compliant | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | X | X | ✓ | ✓ |
| 29. | Smoked Developed Compliant | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | X | X | ✓ | ✓ |
| 30. | Exceptional Wear 25 years | X | X | X | X | X | X | X | X | X | ✓ |
| 31. | International Marine Organisation Approved (I.M.O.) | X | X | X | X | X | X | X | X | X | ✓ |
| 32. | Range of Sizes | X | X | X | X | X | X | X | X | ✓ | ✓ |
| 33. | Range of colors | X | ✓ | X | ✓ | ✓ | X | ✓ | ✓ | ✓ | ✓ |
| 34. | Used by Majority of Govt. Specifiers | ✓ | ✓ | X | ✓ | ✓ | X | X | X | X | ✓ |
| 35. | Supply & Installation can be arranged throughout Australia | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| 36. | Can be installed over existing substrates or inlaid | X | X | X | X | X | X | X | X | ✓ | ✓ |
| 37. | Able to follow ground contours & gradients | ✓ | ✓ | ✓ | ✓ | X | X | ✓ | X | ✓ | ✓ |
| 38. | Can be easily scribed to fit angled finishes | X | X | X | X | X | X | ✓ | X | ✓ | ✓ |
| 39. | Will not chip, fracture or crack with substrate movement | X | X | X | X | X | X | X | X | ✓ | ✓ |
| 40. | Proven performance in both internal & external use (both wet & dry) | ✓ | ✓ | ✓ | ✓ | X | ✓ | X | X | ✓ | ✓ |
| 41. | Easy to install peel and stick application for most surfaces | X | X | X | X | X | X | X | ✓ | ✓ | ✓ |
| 42. | Greatest range of sizes and colours in Australia | X | X | X | X | X | X | X | X | X | ✓ |
| 43. | Product is made from a natural renewable resource | X | X | X | X | X | X | X | X | X | ✓ |
| 44. | Made from 70% recycled content. | X | X | X | X | X | X | X | X | X | ✓ |
| 45. | Custom Colors Available | X | X | X | X | X | X | X | X | X | ✓ |
| 46. | Proven 10 year Performance | X | X | X | X | X | X | X | X | X | ✓ |
| 47. | No Major Installation Failures | X | X | ✓ | X | X | ✓ | X | X | X | ✓ |
| 48. | Fast Production Capabilities | X | ✓ | X | X | ✓ | X | ✓ | ✓ | ✓ | X |
| 49. | Can do two tone Colors | X | ✓ | X | X | X | X | X | X | X | ✓ |
| 50. | Comply AS 1428.4.1:2009 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |

Total Score out of 50

21

18

20

14

16

21

17

12

30

47