



## Technical Specifications

### Tactile Indicator Pads

- Dimensions:** Tile sizes are 200 x 200, 300 x 300 & 600 x 300 mm
- Specifications:**
- |                   |                       |
|-------------------|-----------------------|
| Base Thickness is | 2.5mm                 |
| Profile height is | 5.0mm                 |
| Total Thickness   | 7.5mm                 |
| Edges             | Straight on all sides |
- Composition:** Allsafe Flooring's Tactile Pads are made from unique cork and specially formulated synthetic rubber composition. The tactiles are easily fitted, highly durable and provide excellent anti-slip in both wet & dry conditions.
- Types:** Two types are available:
- Warning of Hazard Indicator (large round studded pattern)
  - Direction of Travel Indicator (large ridge pattern)
- Range of Colours:** Available in a range of standard colors in both hazard (HAZ) and directional (DIR) profiles to allow necessary luminance contrast and profile design flexibility. Special colours are available on request.
- Luminance Value:**
- | <i>Part Number</i> | <i>Colour</i> | <i>Description</i> | <i>Luminance Value</i> |
|--------------------|---------------|--------------------|------------------------|
| TPCI               | Ivory         | HAZ & DIR          | 52                     |
| TPCY               | Yellow        | " "                | 44                     |
| TPCG               | Grey          | " "                | 23                     |
| TPCT               | Terracotta    | " "                | 16                     |
| TPCBL              | Blue          | " "                | 10                     |
| TPCBK              | Black         | " "                | 7                      |
- Slip Resistance:** Allsafe Flooring's Tactile Pads provide excellent anti-slip in both wet and dry conditions. Wet testing achieved an R 11 rating when tested in accordance to AS/NZS 4586 Slip Resistance of Pedestrian Surfaces.
- Chemical Resistance:** Allsafe Flooring's Tactile Pads are resistant to most common acids, alkalis, oils and greases.
- Installation:** Allsafe Flooring's Tactile Pads can be installed in most cases with a peel and stick application. Please check with your Allsafe Flooring Centre for more detailed information.
- Australian Standard:** Allsafe Flooring's Tactile Pads fully conform to all aspects of the Australian Standard 1428.4 and AN/NZS 1428 – 1. Tensile strength, hardness, compressibility, density, wear resistance, and ozone resistance.
- Applications:** Allsafe Flooring's Tactile Pads are used by various roads departments, educational facilities, leading local government bodies, sporting associations and commercial operations throughout Australia and overseas.
- Warranty:** Allsafe Flooring warrants its tactile pads within the terms of Allsafe's standard warranty, against specific suitable installations, and when installed correctly and in accordance with Allsafe Flooring installation instructions.